

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
10 March 2005 (10.03.2005)

PCT

(10) International Publication Number
WO 2005/022190 A1

- (51) International Patent Classification⁷: **G01S 5/14**, H04Q 7/36 (74) **Agent:** MAGNUSSON, Monica; Ericsson AB, Patent Unit Radio Networks, S-164 80 Stockholm (SE).
- (21) International Application Number: PCT/SE2003/001367 (81) **Designated States (national):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 3 September 2003 (03.09.2003) (84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (25) Filing Language: English
- (26) Publication Language: English
- (71) **Applicant (for all designated States except US):** TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-164 83 Stockholm (SE).
- (72) **Inventors; and**
- (75) **Inventors/Applicants (for US only):** STENBERG, Per, Anders [SE/SE]; Stackvägen 37, S-191 34 Sollentuna (SE). BERGENLID, Mikael [SE/SE]; Sidensvansvägen 25, S-192 55 Sollentuna (SE). ALTEIR-TUVESSON, Johan [SE/SE]; Östergatan 2, S-371 39 Karlskrona (SE).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: METHOD AND SYSTEM OF POSITIONING



(57) **Abstract:** The present invention relates to cellular mobile radio systems, particularly to systems of more than one co-sited cell/sector. A method and apparatus of satellite assistance for high accuracy positioning not requiring more terrestrial radio sites than one to be involved in positioning is disclosed.

WO 2005/022190 A1

Method and system of positioning

TECHNICAL FIELD OF THE INVENTION

The present invention relates to cellular mobile radio systems, particularly to positioning in such systems.

5 BACKGROUND AND DESCRIPTION OF RELATED ART

Positioning of, e.g., mobile stations making use of inherent information such as received transmission power level is previously known. It is also considered known in prior art to make use of such information from different base
10 stations receiving signals transmitted from the example mobile station for increasing accuracy of the positioning, e.g. by means of triangulation.

There is an increasing demand for positioning from various administrations. Positioning is particularly requested for
15 emergency calls. Accuracy and time to first fix are key parameters in positioning.

For GSM and UMTS there are two methods of positioning of consideration:

1. Cell Global Identity with Timing Advance.
- 20 2. Assisted GPS.

Cell Global Identity with Timing Advance is operable with GSM. It makes use of a Cell Global Identity broadcast from each base station. The Cell Global Identity consequently identifies the base station with which the mobile station
25 is communicating, or the cell on which the mobile station is camping. The distance from the base station is determined by means of a system inherent Timing Advance parameter, compensating for propagation delay time between base station and mobile station. Conclusively, with Cell Global

Identity with Timing Advance the mobile station can be determined to be within a ring-shaped or arc-shaped area within a cell or cell sector, depending on the radiation pattern. Figure 1 illustrates positioning with timing advance for a 120° sector cell with base station «Site» located to a cell «Cell/Sector» corner. A mobile station «MS» is located to a TA band «TA Band» of width equal to the inaccuracy of the timing advance. However, the method does not reveal where within this band the mobile station is located unless more base stations are involved in positioning. I.e. the mobile station «MS» could be anywhere in the shaded area «TA Band» with the same outcome when trying to position it. In UMTS a feature corresponding to Cell Global Identity with Timing Advance is named Cell Identity with Round Trip Time.

Assisted GPS is a satellite positioning system for assisting both GSM and UMTS, as well as optionally other terrestrial radio systems, but requires a GPS (Global Positioning System) receiver and additional signaling and is not compatible with old GSM terminals. A basic assisted GPS system is illustrated in figure 2. GPS position information is received from three satellites «Sat1», «Sat2», «Sat3». To reduce time to first fix, GPS positioning is assisted by coarse terrestrial positioning communicated from base station «Site». Basically, there are two modes of assisted operation, mobile assisted and mobile based. In the former mode, the mobile station determines pseudoranges to the satellites «Sat1», «Sat2», «Sat3» in view as determined from the coarse positioning. The pseudoranges are transferred to the terrestrial network, in which the mobile station position is calculated. In the latter mode of assisted operation, the mobile station determines its position from available data.

U.S. Patent US6321083 discloses a method and arrangement for locating telephone traffic hot spot of a cell. Timing advance informs of mobile station distance from base station with which it is connected. Direction to the mobile station is determined by means of signal strength from two or more adjacent cells.

International Patent Application WO9728456 describes a terminal position location method using received power levels of multiple neighbor beams from an array antenna.

None of the cited documents above discloses co-sited neighbor assisted positioning determining distance between mobile station and base station by means of timing advance and determining mobile station bearing from received signal level and signal level received in a co-sited neighbor cell/sector, where preferably determined positions are stored for various signal level ranges.

SUMMARY OF THE INVENTION

With greater precision there is less ambiguity and services can be focused. Positioning is particularly requested for emergency calls, but for investments to pay off there will most certainly also be other positioning applications. Cell Global Identity with Timing Advance is considered to be too imprecise to attract operators to most such applications.

Time required for determining mobile station position should be as short as possible. Extensive signaling would drain batteries and load both radio interface, between mobile station and base station, and radio access network/core network. Further, to attract operators, the method should be applicable to existing mobile stations.

There is a problem in existing terrestrial positioning methods utilizing propagation time delay, such as E-OTD (Enhanced Observed Time Difference) or O-TDOA (Observed Time Difference of Arrival), requiring communication involving more than one site for, e.g., triangulation as this among other things involves increased signaling for exchange of timing information for determining propagation time delay. Neighboring base stations may also be under control of different base station controllers, BSCs, or radio network controllers, RNCs. Extensive signaling also delays positioning. Upgrading of existing mobile stations may also be required.

A problem of terrestrial positioning methods utilizing received signal levels, requiring communication involving more than one site for, e.g., triangulation is the small correlation of propagation path losses between different sites, rendering the distance estimates less reliable.

It is consequently an object of the present invention to enhance existing positioning methods for increased accuracy.

It is also an object to achieve a system of terrestrial positioning not requiring more than one terrestrial radio site for fast and reliable positioning.

An object is also not to require extensive operator measuring activities for achieving the enhancement.

A further object is not to require more than one co-sited neighboring cell/sector, assisting the serving cell/sector, for positioning.

Another object is to determine mobile station positions without additional signaling draining batteries.

Finally, it is an object to have an enhanced method and system of positioning compatible with existing mobile stations.

These objects are met by a method and system determining a narrow sector segment within which the mobile station is most likely located according to received signal level and co-sited neighbor cell/sector received signal level, where the signal levels are set in relation to stored positions as determined for corresponding signal levels. With timing advance in addition a position can be determined accurately without involving more than a single site.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates positioning with timing advance for a 120° sector cell with base station «Site» located to a cell «Cell/Sector» corner according to prior art.

Figure 2 displays a basic assisted GPS system according to prior art.

Figure 3 illustrates a non-exclusive example dynamic table for table lookup according to the invention.

Figure 4 schematically illustrates the cell/sector azimuth as described in relation to figure 3.

Figure 5 illustrates ECGI with stored positions in relation to received signal levels according to the invention.

Figure 6 schematically illustrates at least one BTS connected to a BSC over an Abis interface.

DESCRIPTION OF PREFERRED EMBODIMENTS

It has been observed that propagation path losses of neighboring cells/sectors of the same site are highly corre-

lated, particularly for propagation paths between the site and mobile stations close to cell/sector border. In an Enhanced Cell Global Identity, ECGI, method and system, preferably with timing advance, the position is enhanced by determining a sector segment within which the mobile station is most likely located according to received signal level and a co-sited neighbor received signal level. With timing advance in addition, an accurate position can be determined without involving more than one site. The positioning precision is improved by storing positions of mobile stations in relation to various signal level intervals. Preferably, the positions for each signal level are received from mobile stations of recent releases including means for complementary or assisting positioning, such as GPS receivers for A-GPS enabled phones.

Preferably bearings from the site to the mobile station, where a bearing is determined for each GPS position, are averaged over various intervals of received signal levels of serving cell/sector or cell/sector where the mobile station is camping and at least one neighboring cell/sector.

A non-exclusive example dynamic table for table lookup is illustrated in figure 3. In the example dynamic table, the received signal ratio is quantized in equal sized intervals. However, the invention also covers signal level ratio intervals of unequal sizes. For each illustrated interval there is a number of registrations forming basis for an azimuth average $\langle \bar{\phi} \rangle$, as determined from respective GPS positions stored together with the azimuth average $\langle \bar{\phi} \rangle$. The azimuth averages $\langle \bar{\phi} \rangle$ are updated for new registrations matching the signal level ratio intervals, respectively. For reasons of simplicity the table is illustrated with only one parameter: the signal ratio interval. More than one signal level ratio can be used as described above, and

also other parameters than signal level ratio can be made use of.

Figure 4 schematically illustrates the cell/sector angles as described in relation to figure 3.

5 Figure 5 illustrates ECGI with complementary or assisting positioning according to the invention. The mobile station continuously performs measurements of received signal strength of neighboring cells (or base stations) for handover purposes. According to prior art specifications, a
10 list of such one or more cells should be transferred to the network for handover control.

The ratio of respective received power in a neighboring cell/sector «N1» and a serving cell/sector «S» determines where on the TA band «TA Band» a mobile station is located.
15 For a given TA band, the direction to the mobile station «MS» is determined from a ratio of respective received power in a neighboring cell/sector «N1» and a serving cell/sector «S». This ratio is used for table look-up in a position table of Serving Mobile Location Center «SMLC»,
20 where averaged angular directions are stored for various intervals of signal level ratios. A second ratio can be determined for an additional co-sited neighboring cell «N2» to be combined with the initially determined ratio to increase accuracy. If there are more than three sectors of
25 the site, corresponding ratios can be determined also for additional number of co-sited neighbors to be included. Quantities other than signal level ratios can also be included as parameters.

As location is determined from power ratios (or differences
30 in dB-scale) according to the invention, absolute references from field test measurements are not required. The high correlation between propagation path losses of differ-

ent cells/sectors of the same site, particularly for mobile stations close to cell/sector borders, further relaxes the need of field test measurements.

Figure 6 schematically illustrates at least one Base Trans-
5 ceiver System «BTS» connected to a BSC (Base Station Controller) «BSC» over an Abis interface «Abis». The Base Station Controller is connected to an SMLC (Serving Mobile Location Center) «SMLC» over an Lb interface «Lb». The SMLC can be integrated in BSC or MSC or be a standalone device.
10 vice. In the latter two cases also other base station controllers are connected to the SMLC in most implementations.

In a preferred mode of the invention, for a Mobile Station to be positioned received signal levels from the base transceiver system «BTS» are averaged in a locating function
15 tion of base station controller «BSC». The signal levels delivered to SMLC thereby become less noisy and more stable. Further, excessive transmissions in the fixed network are avoided by averaging early in the transmission chain from BTS to SMLC. In, e.g., GSM the earliest feasible occurrence of averaging with sufficient processing capacity
20 is the base station controller. A further advantage is that Abis interface is only marginally additionally loaded as compared to a system not providing for the invention as signal levels, not being averaged, are made available in BSC according to prior art specifications. Preferably the average levels are determined in a locating function of BSC. In addition to prior art systems, base transceiver station «BTS» transmits two signaling levels, one of the served cell and one of the neighbor, in place of only one.
25 Optionally, signaling levels of more than one neighbor cell signaling level (and consequently more than two signaling levels) are transmitted. If signaling levels of both neighbors are included, bearing can be determined from a
30

radio/difference of the individual ratios/differences or directly from a ratio/difference of neighbor signal levels. The base station includes the received signal level of the served cell/sector and at least one co-sited neighboring
5 cell/sector. Preferably, the cell or cells to be included are selected from those signal levels of co-sited cell or cells highest ranked in the locating function. No averaging in SMLC would be required. Further, a requirement on averaging in SMLC would violate present GSM-standardiza-
10 tion.

In one realization of the invention signal levels from a mobile station of up to 32 neighbor cells/sectors can be averaged.

When the invention is applied to e.g. GSM, the averaged
15 level is preferably included in a BSSLAP TA Response to SMLC in response to a BSSLAP TA Request. Thereby, signaling load in the Lb, or corresponding, interface would be reduced, and there would be less noise in the resulting position estimate.

20 A person skilled in the art readily understands that the receiver and transmitter properties of a BTS or an MS are general in nature. The use of concepts such as BTS, BSC, MSC, SMLC or MS within this patent application is not intended to limit the invention only to devices associated
25 with these acronyms. It concerns all devices operating correspondingly, or being obvious to adapt thereto by a person skilled in the art, in relation to the invention. As an explicit non-exclusive example the invention relates to Base Station Controllers of GSM as well as Radio Network
30 Controllers, RNCs, of UMTS.

The invention is not intended to be limited only to the embodiments described in detail above. Changes and modifica-

tions may be made without departing from the invention. It covers all modifications within the scope of the following claims.

CLAIMS

1. A method of positioning a radio transmitter c h a r -
a c t e r i z e d i n that distance to a receiver of
known position is determined according to a parameter re-
flecting propagation delay time and that direction from the
5 receiver to the transmitter is determined from a respective
at least one parameter reflecting received signal level in
a cell/sector where the transmitter is camping or being
served and signal level in a co-sited cell/sector, the pa-
rameter determining direction from stored assisting posi-
10 tion data.
2. The method according to claim 1 c h a r a c t e r -
i z e d i n that the assisting position data is classi-
fied in intervals of one or more parameters.
3. The method according to claim 2 c h a r a c t e r -
15 i z e d i n that the position data in each interval is
averaged over the interval of each of the one or more pa-
rameters.
4. The method according to claim 3 c h a r a c t e r -
i z e d i n that the one or more parameters include re-
20 ceived signal level.
5. The method according to claim 3 c h a r a c t e r -
i z e d i n that the one or more parameters include tim-
ing advance.
6. The method according to claim 3 c h a r a c t e r -
25 i z e d i n that the stored assisting position data is
average position data.
7. The method according to claim 1 c h a r a c t e r -
i z e d i n that the assisting position data is GPS or
other satellite positioning system position data.

8. The method according to claim 7 c h a r a c t e r -
i z e d i n that for a public mobile radio communication
system with a plurality of subscriber receivers the assist-
ing position data is received from one or more subscriber
5 receivers.

9. The method according to claim 1 c h a r a c t e r -
i z e d i n that the co-sited cell/sector is at least one
of the cells/sectors being immediate neighbors of the cell
where the transmitter is camping or being served.

10 10. The method according to claim 1 c h a r a c t e r -
i z e d i n that direction to the transmitter is deter-
mined by forming a linear scale ratio of or dB-scale dif-
ference between the neighbor cell/sector received level and
received level of the cell/sector where the transmitter is
15 camping or being served.

11. The method according to claim 1 c h a r a c t e r -
i z e d i n that determination of transmitter positioning
includes cell/sector identity.

12. The method according to claim 1 c h a r a c t e r -
20 i z e d i n that the received signal level is averaged
prior to forming a basis for positioning.

13. The method according to claim 12 c h a r a c t e r -
i z e d i n that the average is formed in a network con-
trol element.

25 14. The method according to claim 13 c h a r a c t e r -
i z e d i n that the network control element is an entity
most closely connected to the receiver entity over a stan-
dardized interface.

15. The method according to claim 14 c h a r a c t e r -
i z e d i n that the entity most closely connected to the
receiver is a base station controller.

16. The method according to claim 14 c h a r a c t e r -
5 i z e d i n that the entity most closely connected to the
receiver is a radio network controller.

17. A device of positioning a radio transmitter c h a r -
a c t e r i z e d b y processing means for determining
distance to a receiver of known position according to at
10 least one parameter reflecting propagation delay time and
direction from the receiver to the transmitter from a re-
spective parameter reflecting received signal level in a
cell/sector where the transmitter is camping or being
served and signal level in a co-sited cell/sector, the pa-
15 rameter determining direction from stored assisting posi-
tion data; and storage means for storing of assisting posi-
tion data in relation to the at least one parameter.

18. The device according to claim 17 c h a r a c t e r -
i z e d i n that the assisting position data is classi-
20 fied in intervals of one or more parameters.

19. The device according to claim 18 c h a r a c t e r -
i z e d b y processing means for averaging position data
in each interval over the interval of each of the one or
more parameters.

20. The device according to claim 19 c h a r a c t e r -
25 i z e d i n that the one or more parameters include re-
ceived signal level.

21. The device according to claim 19 c h a r a c t e r -
i z e d i n that the one or more parameters include tim-
30 ing advance.

22. The device according to claim 19 c h a r a c t e r -
i z e d i n that the stored assisting position data is
average position data.

23. The device according to claim 17 c h a r a c t e r -
5 i z e d i n that the assisting position data is GPS or
other satellite positioning system position data.

24. The device according to claim 7 c h a r a c t e r -
i z e d i n that for a public mobile radio communication
system with a plurality of subscriber receivers the assist-
10 ing position data is received from one or more subscriber
receivers.

25. The device according to claim 17 c h a r a c t e r -
i z e d i n that the co-sited cell/sector is at least one
of the cells/sectors being immediate neighbors of the cell
15 where the transmitter is camping or being served.

26. The device according to claim 17 c h a r a c t e r -
i z e d i n that direction to the transmitter is deter-
mined by forming a ratio of the neighbor cell/sector re-
ceived level and received level of cell/sector where the
20 transmitter is camping or being served.

27. The device according to claim 17 c h a r a c t e r -
i z e d b y the processing means including cell/sector
identity determination of transmitter positioning.

28. The device according to claim 17 c h a r a c t e r -
25 i z e d b y the processing means forming a time average
of received signal level prior to forming a basis for posi-
tioning.

29. The device according to claim 28 c h a r a c t e r -
i z e d i n that the average is formed in a network con-
30 trol element.

30. The device according to claim 29 c h a r a c t e r -
i z e d i n that the network control element is an entity
most closely connected to the receiver entity over a stan-
dardized interface.

5 31. The device according to claim 30 c h a r a c t e r -
i z e d i n that the entity most closely connected to the
receiver is a base station controller.

32. The device according to claim 30 c h a r a c t e r -
i z e d i n that the entity most closely connected to the
10 receiver is a radio network controller.

33. Radio communication system c h a r a c t e r i z e d
b y means for carrying out the method in any of claims
1-16.

34. Radio communication system c h a r a c t e r i z e d
15 b y a plurality of devices in any of claims 17-32.

1/5




Fig. 1

2/5





Fig. 2

3/5

Ratio (dB)	$\bar{\varphi}$ (deg)	No. of regs.
>0	60	1253
0 - -2	59	1527
-2 - -4	58	839
-4 - -6	56	981
-6 - -8	54	1168
...
-50 - -52	0	2548
...
-70 - -72	-40	225
...

Fig. 3**Fig. 4**

4/5




Fig. 5




Fig. 6

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 2003/001367

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: G01S 5/14, H04Q 7/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04Q, G01S, H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9727711 A1 (NOKIA TELECOMMUNICATIONS OY), 31 July 1997 (31.07.1997), page 10, line 28 - page 14, line 23, figures 2-5 --	1-34
A	US 6321083 B1 (TOMI VAARA ET AL), 20 November 2001 (20.11.2001), column 2, line 8 - column 3, line 25 --	1-34
A	US 6266534 B1 (ALEX K. RAITH ET AL), 24 July 2001 (24.07.2001), column 2, line 31 - line 62 --	1-34
A	WO 9728456 A1 (ERICSSON INC.), 7 August 1997 (07.08.1997), page 2, line 27 - page 3, line 11 --	1-34

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

23 February 2004

Date of mailing of the international search report

04 -03- 2004

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Fredrik Blomqvist/mj
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 2003/001367

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5907809 A (KARL MOLNAR ET AL), 25 May 1999 (25.05.1999), column 2, line 36 - line 56 --	1-34
A	GB 2307142 A (MOTOROLA LIMITED), 14 May 1997 (14.05.1997), page 3, line 12 - line 30; page 5, line 30 - page 6, line 18 -- -----	1-34

INTERNATIONAL SEARCH REPORT

information on patent family members

24/12/2003

International application No.

PCT/SE 2003/001367

WO	9727711	A1	31/07/1997	AU	1547597 A	20/08/1997
				FI	2659 U	29/11/1996
				FI	960381 A,V	27/07/1997
<hr/>						
US	6321083	B1	20/11/2001	AU	4463197 A	05/05/1998
				CA	2267801 A	16/04/1998
				EP	0932993 A	04/08/1999
				FI	103629 B	00/00/0000
				FI	964066 A	11/04/1998
				WO	9816078 A	16/04/1998
				ZA	9708741 A	16/04/1998
<hr/>						
US	6266534	B1	24/07/2001	AU	742151 B	20/12/2001
				AU	6954898 A	13/11/1998
				BR	9808954 A	01/08/2000
				CN	1261436 T	26/07/2000
				EP	0977999 A	09/02/2000
				JP	2001523337 T	20/11/2001
				NZ	500344 A	30/11/2001
				TW	456121 B	00/00/0000
				US	6040800 A	21/03/2000
				WO	9848578 A	29/10/1998
<hr/>						
WO	9728456	A1	07/08/1997	AU	727038 B	30/11/2000
				AU	1857997 A	22/08/1997
				CA	2244993 A	07/08/1997
				CN	1210590 A	10/03/1999
				DE	69705931 D,T	22/11/2001
				EP	0879423 A,B	25/11/1998
				SE	0879423 T3	
				JP	2000504185 T	04/04/2000
				US	5907809 A	25/05/1999
				US	6684071 B	27/01/2004

INTERNATIONAL SEARCH REPORT

Information on patent family members

24/12/2003

International application No.

PCT/SE 2003/001367

US	5907809	A	25/05/1999	AU	4481797	A	14/04/1998
				CN	1115568	B	23/07/2003
				CN	1236437	A	24/11/1999
				EP	0927362	A	07/07/1999
				JP	2001500970	T	23/01/2001
				WO	9812571	A	26/03/1998
				AU	727038	B	30/11/2000
				AU	1857997	A	22/08/1997
				CA	2244993	A	07/08/1997
				CN	1210590	A	10/03/1999
				DE	69705931	D,T	22/11/2001
				EP	0879423	A,B	25/11/1998
				SE	0879423	T3	
				JP	2000504185	T	04/04/2000
				US	6684071	B	27/01/2004
				WO	9728456	A	07/08/1997
				AT	197860	T	15/12/2000
				AU	680348	B	24/07/1997
				AU	1725895	A	01/08/1995
				BR	9505638	A	09/01/1996
				CA	2156738	A	13/07/1995
				CN	1071979	B	26/09/2001
				CN	1124082	A	05/06/1996
				DE	69519484	D,T	05/04/2001
				EG	20504	A	30/06/1999
				EP	0662758	A,B	12/07/1995
				FI	954209	A	08/09/1995
				JP	8510610	T	05/11/1996
				SG	55053	A	21/12/1998
				US	6195555	B	27/02/2001
				US	6418319	B	09/07/2002
				US	6542716	B	01/04/2003
				US	2001004595	A	21/06/2001
				WO	9519094	A	13/07/1995
				ZA	9500170	A	12/12/1995
				AU	1524595	A	01/08/1995
				BR	9505640	A	09/01/1996
				CA	2157182	A	13/07/1995
				CN	1077367	B	02/01/2002
				CN	1124075	A	05/06/1996
				CN	1345129	A	17/04/2002
				CN	1345130	A	17/04/2002
				CN	1345133	A	17/04/2002
				CN	1349310	A	15/05/2002
				CN	1349314	A	15/05/2002
				CN	1349315	A	15/05/2002
				EP	0688482	A	27/12/1995
				FI	954210	A	19/10/1995
				JP	8510609	T	05/11/1996
				US	5555257	A	10/09/1996
				US	5594941	A	14/01/1997
				US	5619503	A	08/04/1997
				US	5631898	A	20/05/1997
				US	5708971	A	13/01/1998
				US	5790606	A	04/08/1998

INTERNATIONAL SEARCH REPORT

Information on patent family members

24/12/2003

International application No.

PCT/SE 2003/001367

US 5907809 A 25/05/1999

US 5812947 A 22/09/1998

US 5848060 A 08/12/1998

US 5937015 A 10/08/1999

US 5940742 A 17/08/1999

US 6088593 A 11/07/2000

US 6148041 A 14/11/2000

WO 9519078 A 13/07/1995

GB 2307142 A 14/05/1997

GB 9522860 D 00/00/0000